


42,43 Double Row(d 10-75mm)



select	Inquiry	Bearing designations	Boundary dimensions mm			Basic load ratings(kN)		Weight Kg
			d	D	B	Dynamic(Cr)	Static(Cor)	
4214A	70	125	31	70200	73500	1.5		
4313A	65	140	48	121000	106000	3.25		
4213A		120	31	67600	67000	1.45		
4312A	60	130	46	112000	98000	2.65		
4212A		110	28	57200	55000	1.1		
4311A	55	120	43	97500	83000	2.15		
4211A		100	25	44900	44000	0.8		
4310A		110	40	81900	69500	1.7		
4210A	50	90	23	41000	40000	0.58		
4309A	45	100	36	68900	56000	1.25		
4209A		85	23	39000	36000	0.54		
4308A		90	33	55900	45000	0.95		
4208A	40	80	23	37100	32500	0.5		
4307A		80	31	50700	38000	0.69		
4207A	35	72	23	35100	28500	0.4		
4306A		72	27	41000	30000	0.5		
4206A	30	62	20	26000	20800	0.26		
4305A	25	62	24	31900	22400	0.34		
4205A		52	18	19000	14600	0.16		
4304A	20	52	21	23400	16000	0.21		

42,43 Double Row(d 10-75mm)

4204A		47	18	17800	12500	0.14	
4303A	17	47	19	19500	13200	0.16	
4203A		40	16	14800	9500	0.09	
4302A	15	42	17	14800	9500	0.12	
4202A		35	14	11900	7500	0.059	
4301A	12	37	17	13000	7800	0.092	
4201A		32	14	10600	6200	0.053	
4200A	10	30	14	9230	5200	0.049	
4215A	75	130	31	72800	80000	1.6	
4216A		140	33	80600	90000	2	