


Double Row 30..2RS38..2RS30..2Z 38..2Z(d 5-80mm)



select	Inquiry	Bearing designations	Boundary dimensions □mm□			Basic load ratings(kN)		Weight Kg
			d	D	B	Dynamic(Cr)	Static(Cor)	
3005 2RS	25	47	16	15500	11100	0.1		
3804 2Z		32	10	5600	4850	0.02		
3804 2RS		32	10	5600	4850	0.02		
3004 2Z		42	16	14500	9600	0.08		
3004 2RS	20	42	16	14500	9600	0.08		
3803 2Z		26	7	2480	1200	0.016		
38032RS		26	7	2480	1200	0.016		
3003 2Z		35	14	9200	6200	0.042		
30032RS	17	35	14	9200	6200	0.042		
3802 2Z		24	7	2340	1880	0.009		
38022RS		24	7	2340	1880	0.009		
3002 2Z		32	13	8600	5400	0.036		
30022RS	15	32	13	8600	5400	0.036		
3001 2Z		28	12	6200	3750	0.025		
3001 2RS	12	28	12	6200	3750	0.025		
3000 2Z		26	12	5700	3250	0.022		
3000 2RS	10	26	12	5700	3250	0.022		
30/8 2Z		22	11	5200	2610	0.02		
30/8 2RS	8	22	11	5200	2610	0.02		
30/7 2Z		19	10	3650	1700	0.012		

Double Row 30..2RS38..2RS30..2Z 38..2Z(d 5-80mm)

30/7 2RS	7	19	10	3650	1700	0.012
30/6 2Z		17	9	3100	1400	0.01
30/6 2RS	6	17	9	3100	1400	0.01
30/5 2Z		14	7	1810	950	0.008
30/5 2RS	5	14	7	1810	950	0.008
3005 2Z		47	16	15500	11100	0.1
3805 2RS		37	10	6000	5600	0.025
3805 2Z		37	10	6000	5600	0.025
3006 2RS	30	55	19	20300	13500	0.16
3006 2Z		55	19	20300	13500	0.16